

MSA G1™ City Edition SCBA

Product Specifications

4500 psig



I. Approvals

- Apparatus shall be approved by the National Institute for Occupational Safety and Health (NIOSH), under 42 CFR, Part 84 for chemical, biological, radiological, and nuclear protection (CBRN) with 30-, 45-, 60-minute-rated service life and compliant with all requirements of the National Fire Protection Association's 2025 Edition of NFPA-1970 Standard on Protective Ensembles for Structural and Proximity Firefighting, Work Apparel, Open-Circuit Self-Contained Breathing Apparatus (SCBA) for Emergency Services, and Personal Alert Safety Systems (PASS).
- Units equipped with accountability system must meet minimum requirements for FCC part 15.

II. Specific Requirements

Facepiece

1. Facepiece shall have removable inhalation check valve to prevent exhaled air from entering and contaminating regulator (demand valve).
2. Facepiece shall have open port to provide minimal breathing resistance when regulator is not attached.
3. Facepiece shall not contain electronic components.
4. Facepiece shall provide means to display to user with visual indicators for HUD.
5. Facepiece shall have icon for HUD system status indicators.
6. Facepiece shall have regulator attachment that does not bear any weight on lens.
7. Facepiece shall have effective field of view of 86% and overlapping field of view of 122% without attached component.
8. Facepiece shall be available in three sizes in Hycar Rubber (small, medium, large).
9. Facepiece shall have nose cup comprised of silicone rubber and available in three sizes (small, medium, large).
10. Facepiece shall have one head harness options constructed of flame/heat resistant assembly: Kevlar 4-pt. adjustable with stiffener.
11. Facepiece shall have universal lens that can be used with all three facepiece sizes, shall be comprised of non-shatter type material and shall be field-replaceable.
12. Lens shall be hard-coated on outside and anti-fog coated on inside
13. Facepiece shall have optional flame/heat-resistant fabric or rubber neck strap to carry facepiece in ready position for quick donning.
14. Facepiece shall have removable speaking diaphragm with aluminum-coated membrane, suitably protected and located centrally on facepiece for optimal voice projection.
15. Facepiece shall have exhalation valve that is to be serviceable without special tools.
16. Facepiece shall be capable of water submersion for cleaning and disinfection.
17. Facepiece provides RFID chip for optional asset and maintenance tracking.
18. Facepiece shall not include additional modules or batteries.

Mask-Mounted Regulator (Demand Valve): Push-to-Connect

1. When doffing regulator, regulator disengagement shall simultaneously stop air flow and release regulator.
2. Regulator shall house electronic module that functions as microphone and HUD system.
3. Regulator shall be equipped with variable flow bypass.
4. Regulator shall not have exposed wiring in order to prevent snags and increase product durability.
5. Regulator shall have one cover option: hard cover.

continued next page

WHEN YOU GO IN, WE GO IN WITH YOU.

6. Regulator shall have fewer than 35 parts that are easily replaceable without special tools
7. Regulator shall have one option for air-supply hose: Quick-connect hose that terminates on shoulder in front of user
8. Regulator must be equipped with positive protection Tetraplex Shield membrane that covers diaphragm, preventing permeation of CBRN agents.
9. Regulator shall have RFID chip for optional asset and maintenance tracking.

Heads-Up Display (HUD)

1. Heads-Up Display (HUD) System shall be integrated within regulator, eliminating snag hazards and increasing product durability.
2. HUD shall be powered from central power system.
3. HUD System shall eliminate cross-talk among firefighters.
4. HUD System shall be immune to radio frequency interference (RFI) and must function properly in close proximity to fire service hand-held radios.
5. **HUD System shall separate pressure indicators from status indicators:**
 - 1) Left: status indicators.
 - 2) Right: pressure indicators.
6. **HUD system shall provide user with remaining cylinder air volume, available in four increments through series of four colored LEDs:**

	4500
Four green lights	71-100% service pressure
Three green lights	46-70% service pressure
Two flashing amber lights	32-45% service pressure
One flashing red light	0-29% service pressure

7. HUD status indicators shall be icon-based and display battery life warning, PASS alarms, EVACUATE indicator, and secondary alarm indicator.
8. HUD shall incorporate photoelectric sensor that senses ambient light conditions, automatically adjusting display to one of multiple pre-programmed light intensities.
9. Buddy lights shall be visible from outside of firefighter's facepiece.
10. **HUD system shall allow user to select from four modes of operation:**
 - 1) Continuous pressure mode that shall always have pressure LEDs on.
 - 2) Intermittent pressure mode that shall turn on first three increments when reached for 20 seconds.
 - 3) Oscillating pressure mode that shall brighten and dim LEDs every 20 seconds.
 - 4) Mixed pressure mode that shall turn on first two increments when reached for 20 seconds and last two increments are in continuous mode.
11. HUD shall be field-removable and replaceable without use of special tools.

Universal Air Connection (UAC)

1. **System shall be capable of:**
 - 1) Refill within immediately dangerous to life or health (IDLH) atmospheres.
 - 2) Transfiling between two SCBA wearers (connection allows for donation and receipt .of air), providing emergency breathing system (EBS) while maintaining NIOSH approvals.
 - 3) Quickly refilling (approximately one-minute duration) SCBA cylinder from mobile compressor, cascade system or RIT pack.
 - 4) Extending wearer's air supply over longer duration when remote cascade system or other compressed gas source is located within remote area.
2. Primary UAC shall be illuminated when supply pressure reaches Low Pressure Warning Alarm or can be configured to optional medium pressure warning alarm.
3. SCBA shall have secondary options for UAC to be mounted on user's waist.
4. Transfiling is possible only with 4500 psig.

Pressure Reducer (First-Stage Regulator) with Primary Low-Pressure Warning Device

1. Pressure reducer shall incorporate downstream valve to ensure fail-safe design when in open position.
2. Pressure reducer shall incorporate bell alarm mechanism.
3. Bell alarm mechanism shall be an air-actuated, continuously ringing audible warning alarm, automatically operating when supply cylinder air pressure reaches approximately 31% for 4500 systems of rated service pressure.
4. Bell alarm mechanism shall cover multiple levels of frequencies to cover all hearing levels.
5. Bell alarm mechanism shall be user-accessible while wearing SCBA.
6. Pressure reducer reduces cylinder pressure to outlet pressure not to exceed 115 psi; outlet pressure must be adjustable.
7. Pressure reducer shall have flow capacity of 700 liters per minute at full pressure.
8. Pressure reducer shall have two options for cylinder connection type: threaded or quick-connect.
9. Quick-connect connection shall not be removable from cylinder while under pressure.
10. Pressure reducer shall have one option for cylinder connection location: remote connection.
11. Pressure reducer shall be capable of converting from threaded to quick-connect or vice versa.
12. Pressure reducer body shall be constructed of high-strength aluminum alloy and anodized with Teflon hard coat to minimize corrosion and wear of internal and external components.
13. Pressure reducer shall be sealed system that does not allow moisture to enter valve components.
14. Pressure reducer shall have no more than 42 individual regulator replacement parts.
15. Pressure reducer shall not require special tools for disassembly.
16. Pressure reducer shall have two accessory ports, one medium pressure and one high pressure.

Cylinders

1. Cylinders with 4500 psig operating pressure must be available in 30-, 45- and 60-minute durations.
2. Cylinders must be available in one operating pressure: 4500 psig
3. Cylinder shall be constructed of deep-drawn, seamless aluminum liner that is fully wound over entire surface (except for thick neck area) with high-strength carbon fiber filaments impregnated with epoxy resin.
4. Cylinder shall contain cylinder valve that shall incorporate pressure gauge to indicate cylinder pressure at all times. Pressure gauge face shall be luminescent. Hand wheel shall be placed at 90° angle from cylinder axis.
5. Remote connection available as threaded or quick connect.
6. Cylinder valve shall incorporate flow control insert to limit air flow over hand wheel's first half-rotation, minimizing propulsion thrust in event that cylinder is mishandled.
7. Cylinder valve shall incorporate CGA thread that can be converted to quick-connect cylinder without special tools.
8. Cylinder shall have bracket and boot that can be user-installed and provide positioning and added security of cylinder to backplate.
9. Cylinder shall be available with locking handwheel option.

PASS Device

1. PASS device shall contain power, control and battery modules.
2. Power module shall provide power to all electronic SCBA components from battery module and act as central power system.
3. Power module shall act as central command center, distributing all information and data among electronic components.
4. Battery module shall be powered by one lithium-ion rechargeable battery.
5. PASS device shall design for battery level check and removal of batteries while SCBA remains in jump seat.
6. Power module shall be capable of illuminating UAC fitting when supply cylinder reaches 31% for 4500 systems of rated service pressure.

continued next page

7. Control module shall have analog and digital display for added redundancy. Analog gauge must be positioned above digital display as viewed by user
8. Control module shall be equipped with full color graphical display. Display shall be reprogrammable and capable of future integrations. Display's background color coordinates with HUD pressure status.
9. Control module shall automatically provide information to user when placed in upright position. Device can be manually activated by pressuring reset button.
10. PASS device shall use single line to connect power and control module.
11. Control module shall have two reset buttons that perform same function no matter which button is pressed.
12. Control module shall have alarm button to activate full alarm and is to be illuminated.
13. PASS device shall be capable of being reprogrammed to fire department standard operating procedures (SOP). Using PC software program, configuration tag can be created and tagged on each device needed. **Reprogramming options are as follows:**
 - 1) Medium pressure alarm.
 - 2) Pressure drop alarm.
 - 3) Primary temperature alarm.
 - 4) Secondary temperature alarm.
 - 5) Audible low-pressure alarm.
14. PASS device shall be equipped with buddy lights on firefighter's front and back and viewable from 360° view; two buddy lights on front of user and four buddy lights in back of user.
15. PASS device shall have colored buddy lights: green, yellow, and red.
16. Power module shall be equipped with dual sound emitters; sound emitters shall perform at minimum 100 dBa in room temperature.
17. PASS device shall be capable of storing up to 36 hours of use information in event log form that are generated each time SCBA is pressurized. Event logs must indicate on/off cycles, alarms, alarm reset, and tagging events.
18. PASS device shall be capable of storing periodic logs. Periodic logs must indicate cylinder pressure for each SCBA pressurization stored at 30-second intervals.
19. PASS device's event and periodic logs shall provide ability to download to personal computer for maintenance records or for use in incident investigations.
20. PASS device shall be immune to radio frequency interference (RFI) and must function properly in close proximity of fire service hand-held radios.
21. PASS device shall have optional time-remaining display. Time remaining function must update calculations every 30 seconds based upon user's previous three minutes of air consumption. Initial calculation will appear after three minutes. Calculations can be made to zero pressure, low pressure alarm or medium pressure alarm.
22. PASS device shall employ gasket perimeter seal to provide highest protection level against water ingress, while providing ability to upgrade or repair electronics.
23. PASS device shall be capable of electronically storing user's name into memory via ID tag
24. PASS device shall be removable with no more than two screws.
25. Control module shall have service mode that provides ability to see number of hours used, connect to PC and firmware versions.
26. Control module shall incorporate rubber boot for added protection and is to be replaceable.
27. Power and Control Modules shall have RFID chip for optional asset and maintenance tracking.
28. Power Module shall include a tracking device with the ability for a handheld device to search for an SCBA. This handheld device must have thermal imaging capability with edge detection.

Speaker Module

1. Speaker module shall provide amplified speech that removes inhalation breath noise.
2. Speaker module shall provide at minimum, 70 dBa output.
3. Speaker module shall turn on and off with PASS device.

continued next page

4. Speaker module shall be powered by central power system.
5. Speaker module shall be positioned on chest and attached to the right shoulder strap.
6. Speaker module shall be capable of being mounted on either left or right shoulder strap.
7. Speaker module shall easily be attached and removed without special tools.
8. Speaker module shall have light to indicate that device is powered on.
9. Speaker module shall have on/off button to allow user to manually power off as needed.

Carrier & Harness

1. Shoulder harness shall have separate left and right pads for easier and less costly replacement
2. Shoulder harness shall have retro-reflective markings for better visibility within low light conditions
3. Shoulder harness shall have friction pads on shoulders to prevent slippage
4. Shoulder harness shall be available in serviceable tunnel
5. Shoulder harness shall have improved color stability up to 600°F
6. Shoulder harness shall be capable of washing at least 40 times while maintaining color fastness
7. Harness design shall have Kevlar webbing.
8. **Waist pad shall be available in two options:**
 - 1) Low-Profile swiveling—basic pad with straps attaching directly to backplate.
 - 2) Adjustable swiveling—standard pad attached to metal bracket that has three positions and automatically centers.
9. Adjustable swiveling waist pad shall be one-handed operation and can be performed while on user's back.
10. Backplate shall be capable of accepting both waist pad designs.
11. Backplate shall have two side handles and one top handle that are accessible with gloved hand.
12. Backplate side handles shall be capable of 500 lbs. of static force.
13. Backplate top handle shall be capable of 1000 lbs. of static force.
14. Backplate cylinder band shall be available in metal.
15. Waist pad shall be of rigid construction to allow for easy donning and support.
16. Waist straps shall be double-pull forward design.
17. The front of the end termination on the pull straps shall have an option to include reflective cotton.
18. Cylinder retention shall include an optional slide lock retainer and a positive stop to hold in place without adding a second action to remove the cylinder.

Weight

1. Weight of SCBA shall not exceed 24 lbs.
2. Weight of facepiece (without regulator, with communications) shall not exceed 1.4 lbs.
3. Weight of cylinder and valve assemblies (empty) shall not exceed:

CYLINDER TYPE	WEIGHT
Carbon-wrapped 30 minute	7 lbs. 4 oz.
Carbon-wrapped 45 minute LP	9 lbs. 7 oz.
Carbon-wrapped 45 minute Stubby	9 lbs. 10 oz.
Carbon-wrapped 60 minute	11 lbs. 12 oz.

Asset & Maintenance Tracking Software

1. Should work on both desktop as well as mobile device.
2. Must have the ability to track and report on assets including but not limited to SCBA, Facepieces, Cylinders, and Parts.
3. Must have the ability to track and report on Maintenance, including but not limited to Work Orders, cylinder fill and which fill station was used, cylinder hydro static testing, SCBA flow tests.
4. Must also have the ability to track and report on Fit Tests.
5. Must also have the ability to track and report on Purchase Orders.
6. Must have the ability to alert the user on any upcoming fit tests, cylinder hydro static testing, and SCBA overhaul that may be needed.
7. Information must be stored in a manner that is updated seamlessly and instantly across all devices.

Power Source

1. All components of the SCBA must be powered from single power source.
2. Rechargeable battery must weigh no more than 11lb.
3. Rechargeable battery must recharge from full discharge in less than 7 hours.
4. Rechargeable battery recharge temperature range must fall between 32°F and 104°F.
5. Rechargeable battery will have full charge capabilities for no less than 300 cycles.
6. Rechargeable battery Charger must be a smart charger which will rapid charge, analyze condition, and switch to trickle charge mode when charge is complete.
7. Rechargeable battery Charger must have charging indication lights.

Upgradeability

1. Must be Bluetooth® enabled.
2. Must be able to receive updates to firmware via a Bluetooth® connection.
3. Control module must have Bluetooth® icon visible to display connection status.
4. Must have the ability to upgrade standard control module to integrated thermal imaging camera control module.

Search & Rescue

1. Must have option for SCBA to be searchable through an independent hand-held device
2. Searching device must have integrated thermal imaging and cellular connectivity for incident command connection.
3. Must have ability to have unlimited searchers via hand-held device for a singular SCBA when in alarm.
4. Independent search and rescue network must work regardless of cellular connectivity.
5. Searching device must include GPS capabilities.
6. Searching device must be capable of Bluetooth® pairing for SCBA interoperability.



Telemetry Network

1. Must have option to have telemetry enabled SCBA.
2. Must be able to connect 50 SCBA to single HUB/connectivity device at one time.
3. HUB/connectivity device must be able to connect to cloud via internet connection or LTE.
4. HUB/connectivity device must be IP67 rated.
5. All SCBA air pressure and alarm data must be able to be saved in a cloud network.
6. All cloud platforms must be certified by ISO 9001:2015, ensuring compliance with global quality standards.
7. All SCBA air pressure and alarm data must have the capability to be shared via cloud-to-cloud API with third party incident command software platforms.

Our Mission

MSA's mission is to see to it that men and women may work in safety and that they, their families, and their communities may live in health throughout the world.

MSA: WHEN YOU GO IN, WE GO IN WITH YOU.

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit ***MSAsafety.com/offices***.